



## Cabinet Dimensions:

	External	Internal
Width (mm):	1205	1120
Depth (mm):	660	450
Height (mm):	1300 (std. castors)	800

Weight (kg):	150
Capacity (L):	403
Footprint (m <sup>2</sup> ):	0.8

Electrical Voltage (V):	220-240
Electrical Ampere (A):	3.5
Electrical Frequency (Hz):	50

MEPS TEC:	7.50 kwh/24h
Refrigerant:	R290 /150 g

### Dimensional Tolerances

Before installing this cabinet allow for the following dimensional tolerances:

Linear Dimensions	Single Cabinet Dimensions
Less than 1 metre	±5mm
More than 1 metre	-5mm to +10mm
Length of Multiple Cabinets	
At each joint	At each end wall
±5mm	+15mm
-5mm to +10mm	+15mm

**SKOPE**  
Industries Limited

66 Princess St. PO Box 1091  
Christchurch, New Zealand  
New Zealand Freephone: 0900 947 5673  
Australian Freephone: 1800 121 535  
Email: enquiry@skope.co.nz  
Website: www.skope.co.nz

**Model:**  
OD460N

### Description:

Open Deck Open Face POS retail Fridge with Integral, Bottom refrigeration services

### Unless Otherwise Specified:

Folded Dimension:	Overall
Linear Tolerances:	± 0.5mm
Angular Tolerances:	± 0.5mm
Units:	Millimeters

**Scale:**  
1 : 20

**Revision:**

Copyright © SKOPE Industries Limited